



## PRODUCT MANUAL

### Included in the Box

- Killflash
- Lens cloth

Elevation  
Adjustment Dia

Windage  
Adjustment Dia



Power-Off Position  
Indicator

Brightness Knob  
Power On/Off

The windage/elevation  
safety caps can be used  
as a tool for adjustment



Battery Compartment

### Brightness Adjustment

The red dot provides 8 levels of brightness adjustment. Turning the brightness knob clockwise from the power-off position can adjust the illumination brightness from level 1 (minimum) to level 7.

Turning the brightness knob counterclockwise from power-off position can quickly switch to maximum brightness (level 8).

### Battery Type

AA battery, 1.5 V, Alkaline battery is recommended. It is acceptable to use AA rechargeable battery, 1.2 V.

(To prevent battery leakage, we strongly recommend removing the battery from the device when it will not be used for a long time.)

## SPECS

Length x Width x Height	116 x 62.6 x 78 mm (4.56 x 2.44 x 3.07 inch)
Reticle Color	Red
Illumination Source	LED
Adjustment	1 MOA Per Click
Shock Proof	Acceleration 1000 G with 3.8 Hz and 10 times
Housing Material	6061-T6 Aluminum
Weight (battery not included)	395 g (13.9 oz.)
Power Source	1x AA Battery

Magnification	1x
Exit Pupil Dia.	30 mm
Parallax Setting	100 yds
Eye Relief	Unlimited
Windage Elevation (Up Down)	40 MOA - 40 MOA
Windage Elevation (Right Left)	40 MOA - 40 MOA
Type of Reticle	3 MOA Dot
Lens Coating	Fully Multicoated